

Serial No.: 10/705,550

Attorney Docket No.: 35683.0022

This listing of claims will replace all prior versions of the claims in the application:

**Listing of Claims:**

--Claims 1-3 (Cancelled)

4. (Currently amended) The device of claim 19 [[[3]]] wherein the first portion of the torsion bar is connected by a radially extending connector to the tubular member, and at least one radially extending bushing is located on the torsion bar within the tubular member for maintaining relative radial spacing between the tubular member and the torsion bar.

5. (Currently amended) The device of claim 19 [[[3]]] including first and second spaced apart bracket members supporting the first and second ends of the tubular member, respectively, the lever member being located adjacent the first bracket member and securable to the first bracket member in a plurality of selectable positions for adjusting the torsional bias applied to the torsion bar.

6. (Original) The device of claim 5 wherein each of the first and second bracket members includes an outwardly projecting connector on which a weld plate is mounted for, prior to installation on a conveyor belt system, rotation about a second axis that is substantially parallel to the first axis and sliding movement along the connector lateral to the second axis.

Claim 7 (Cancelled)

8. (Currently amended) The device of claim 20 [[[7]]] wherein each of the first and second bracket members includes an outwardly projecting connector on which a weld plate is mounted for, prior to installation on a conveyor belt system, rotation about a second axis that is substantially parallel to the first axis and sliding movement along the connector lateral to the second axis.

Serial No.: 10/705,550

Attorney Docket No.: 35683.0022

Claims 9-11 (Cancelled)

12. (Currently amended) The device of claim 21 ~~[[11]]~~ wherein the ~~elongate~~ tubular member is defined by an outer wall on which a scraper blade bracket is located, the scraper blade being removably mounted to the scraper blade bracket.

13. (Original) The device of claim 12 wherein the scraper blade is reversible with first and second opposite ends that each have a scraping edge for scrapping the conveyor belt.

14. (Original) The device of claim 13 wherein the scraper blade includes a row of openings along a center line between the first and second opposite ends thereof, the blade being secured to the scraper blade bracket by fasteners extending through the openings.

Claim 15 (Cancelled)

16. (Currently amended) The device of claim 22 ~~[[15]]~~ wherein the first portion of the torsion bar is connected by a radially extending connector to the tubular member, and at least one radially extending bushing is located on the torsion bar within the tubular member for maintaining relative radial spacing between the tubular member and the torsion bar.

17. (Currently Amended) The device of claim 22 ~~[[15]]~~ including first and second spaced apart bracket members connected to the support frame and supporting the first and second ends of the tubular member, respectively, the lever member being located adjacent the first bracket member and securable to the first bracket member in a plurality of selectable positions for adjusting the torsional bias applied to the torsion bar.

18. (Original) The device of claim 17 wherein the lever member has a securing opening therethrough that can be selectively aligned with openings provided through the first bracket member corresponding to the plurality of selectable positions and including a locking pin for

Serial No.: 10/705,550

Attorney Docket No.: 35683.0022

insertion through the securing opening and an aligned one of the openings through the first bracket member to secure the lever member.

19. (New) A conveyor belt scraper tensioning device including:

*an elongate tubular support member mounted to at least partially rotate about a first axis, the tubular member being defined by an outer wall radially spaced apart from the first axis and having a scraper blade bracket located on the outer wall for securing a scraper blade thereto;*

*a torsion bar located substantially within the tubular member along the first axis for imparting a torsional bias to the support member, the torsion bar having a first portion connected to the support member and a further portion spaced apart from and at least partially rotatable relative to the support member; and*

*a lever member connected to the further portion of the torsion bar at a location spaced apart from the first portion for imparting torsional bias on the torsion bar,*

*wherein the tubular member has first and second ends, the first portion of torsion bar being connected to the tubular member near the second end of the tubular member, the lever member being connected to an end of torsion bar that extends beyond the first end of the tubular member.*

20. (New) A conveyor belt scraper tensioning device including:

*a support member mounted to at least partially rotate about a first axis, the support member being radially spaced apart from the first axis and having a scraper blade bracket for securing a scraper blade thereto;*

*a torsion bar located substantially along the first axis for imparting a torsional bias to the support member, the torsion bar having a first portion connected to the support member and a further portion spaced apart from and at least partially rotatable relative to the support member;*

*a lever member connected to the further portion of the torsion bar at a location spaced apart from the first portion for imparting torsional bias on the torsion bar; and*

*first and second spaced apart bracket members supporting the support member at opposite ends thereof, the lever member being located adjacent the first bracket member and*

Serial No.: 10/705,550

Attorney Docket No.: 35683.0022

securable to the first bracket member in a plurality of selectable positions for adjusting the torsional bias applied to the torsion bar.

21. (New) A conveyor belt scraper tensioning device including:

a support member mounted to at least partially rotate about a first axis, the support member being radially spaced apart from the first axis and having a scraper blade bracket for securing a scraper blade thereto;

a torsion bar located substantially along the first axis for imparting a torsional bias to the support member, the torsion bar having a first portion connected to the support member and a further portion spaced apart from and at least partially rotatable relative to the support member;

a lever member connected to the further portion of the torsion bar at a location spaced apart from the first portion for imparting torsional bias on the torsion bar; and

a scraper blade removably mounted to the scraper blade bracket, the scraper blade being reversible with first and second opposite ends that each have a scraping edge for scrapping the conveyor belt, wherein the scraper blade includes a row of openings along a center line between the first and second opposite ends thereof, the scraper blade being secured to the scraper blade bracket by fasteners extending through the openings.

22. (New) In combination with a conveyor belt system having a conveyor belt mounted to a support frame, a scraper blade support device including:

a tubular member having opposite first and second ends mounted to the support frame, the tubular member being at least partially rotatable about an axis that is substantially transverse to a direction of travel of the conveyor belt;

a scraper blade extending outward from the tubular member and having an end for engaging the conveyor belt for removing material therefrom;

a torsion bar extending along the axis inside the tubular member, the torsion bar having a first portion rigidly attached to the tubular member near the second end thereof for imparting a torsional bias thereto and a further portion near the first end of the tubular member that is partially rotatable relative to the tubular member; and

Serial No.: 10/705,550

Attorney Docket No.: 35683.0022

a lever member connected to an end of the torsion bar that extends beyond the first end of the tubular member for imparting a torsional bias to the torsion bar.—